

























IF YOU SMELL GAS

1. Extinguish any open flames, pilot lights and all smoking materials.
2. Do not touch electrical switches.
3. Shut off the gas supply at the tank valve(s) or gas supply connection.
4. Open doors and other ventilating openings.
5. Leave the area until odor cleared and leakage source corrected before using again.
6. Have the gas system checked and repaired.

DO NOT REMOVE/NE PAS ENLEVER

Information, please do not remove/NE PAS ENLEVER

Model	Serial	Installation	Service
1. Model	2. Serial	3. Installation	4. Service
5. Model	6. Serial	7. Installation	8. Service
9. Model	10. Serial	11. Installation	12. Service
13. Model	14. Serial	15. Installation	16. Service
17. Model	18. Serial	19. Installation	20. Service
21. Model	22. Serial	23. Installation	24. Service
25. Model	26. Serial	27. Installation	28. Service
29. Model	30. Serial	31. Installation	32. Service
33. Model	34. Serial	35. Installation	36. Service
37. Model	38. Serial	39. Installation	40. Service
41. Model	42. Serial	43. Installation	44. Service
45. Model	46. Serial	47. Installation	48. Service
49. Model	50. Serial	51. Installation	52. Service
53. Model	54. Serial	55. Installation	56. Service
57. Model	58. Serial	59. Installation	60. Service
61. Model	62. Serial	63. Installation	64. Service
65. Model	66. Serial	67. Installation	68. Service
69. Model	70. Serial	71. Installation	72. Service
73. Model	74. Serial	75. Installation	76. Service
77. Model	78. Serial	79. Installation	80. Service
81. Model	82. Serial	83. Installation	84. Service
85. Model	86. Serial	87. Installation	88. Service
89. Model	90. Serial	91. Installation	92. Service
93. Model	94. Serial	95. Installation	96. Service
97. Model	98. Serial	99. Installation	100. Service





Dometic


Dometic

GAS OPERATION

1. To start the refrigerator turn the knob A to position GAS.
2. Turn the thermostat knob B to position 4.
3. Press the button C to stop and push the button D of the gas lighter. The pointer has to be repeated until the gas is lit at the burner. That can be observed by the RED indicator E on the GREEN field.
4. After the gas is lit keep the button C pressed for 10 seconds. Release the button and check that the RED indicator E is on the GREEN field.

ELECTRIC OPERATION

1. Check that the attachment plug is correctly connected to the main supply.
2. Turn the knob A to desired position for electric operation.
3. Turn the thermostat knob B to position 4.



260 26 77











MPH
km/h

P R N D 21

UNLEADED FUEL ONLY



O/D
OFF

MIRRORS
L R
































Minimum clearances in inches to combustible materials: Top: 0, Sides: 0, Bottom: 0, Back: 1.
Clearances on top of the condenser unit are related to minimum ventilation height as shown in the installation instructions.

Les distances de dégagement minimum (en pouce) par rapport aux matériaux combustibles sont de:
au-dessus: 0, latéralement: 0, en dessous: 1, à l'arrière: 1.
La distance de dégagement au-dessus du condenseur est fonction de la hauteur de ventilation comme indiquée dans les instructions d'installation. 385 05 84

FOR USE WITH APPROVED
VENT KIT, PART No. HP 75



IMPORTANT CONCERNANT LE RÔLE DE
MARQUE 12 V.
Le branchement n'est destiné à être raccordé qu'à des
câbles basse tension et à du courant continu. Il ne doit pas
être raccordé à du courant alternatif de 100, 120 ou 240 volts. Les
câbles du conducteur et la dimension du fusible du branchement
doivent être conformes aux "instructions d'installation et
d'exploitation". Lorsque vous intervenez sur l'appareil, débranchez
le câble de 12 V.

LA PRESSION
When testing the fuel-gas system for leakage the equipment
operator must not be subjected to an internal pressure
exceeding 22 inches of water column (0.96 kPa). When the pressure
operation the inlet gas pressure shall be 11 inches of water
(0.74 kPa).

LA PRESSION D'ALIMENTATION
Lorsque vous vérifiez la pression du système de gaz, le matériel
opérateur ne doit pas être soumis à une pression intérieure
excédant 22 pouces de colonne d'eau (0,96 kPa). Lorsque vous
intervenez sur l'appareil, débranchez le câble de 12 V.

SEMBLY
AND PIR
385 05 84



WARNING
BATTERY FLAMMABLE
EXPLOSIVE
DANGER
DO NOT SMOKING
OR OPEN FLAME
NEAR BATTERY
DO NOT SPARK
TOOL OR WIRE
ENDS TOGETHER
DO NOT REMOVE
BATTERY LIDS
WHILE BATTERY
IS CHARGING
DO NOT REMOVE
BATTERY LIDS
WHILE BATTERY
IS CHARGING
DO NOT REMOVE
BATTERY LIDS
WHILE BATTERY
IS CHARGING

TOTAL BATTERY
WE SELL BATTERIES AND CHARGERS FOR ALL
VEHICLES
WWW.TOTALBATTERY.COM
NATIONWIDE WARRANTY

POTENTIAL
SANITIZE, FLUSH AND DRAIN
BEFORE USING
(SEE INSTRUCTION MANUAL)

PARK-CABLE
HOOK-UP

THIS CONNECTION IS
FOR 110/125 VOLT AC
50 HZ. 20 AMP
MAXIMUM



81CF 30
YOURS TO DISCOVER

